

**OFFICE OF THE MANAGING DIRECTOR  
NHDC LIMITED  
10<sup>th</sup> & 11<sup>th</sup> floor  
VIKAS DEEP, LUCKNOW**

No: NHDC/Reno/HR/

Dated: 31-May-2016

**NOTICE INVITING QUOTATION**

Sealed percentage rate quotations are hereby invited by the undersigned from approved and eligible contractors of CPWD and those of appropriate class of contractors enlisted in the BSNL, Department of Post, MES, Railways and State PWD of Uttar Pradesh for under mentioned work. Last date & time of submission of quotation shall be 14-06-2016 up to 3:00 P.M and same shall be opened at 4:00 P.M on same day .

| S.No. | Name of work  | Estimated cost | Time limit |
|-------|---|----------------|------------|
| 1.    | Renovation of toilets of NHDC Ltd. office at 10 <sup>th</sup> & 11 <sup>th</sup> floor in Vikas Deep Building , Lucknow | Rs.3,24,586.00 | 45 days    |

**Terms & Conditions :**

1. The work shall be carried out as per CPWD Specification.
2. Time allowed for completion of work shall be **45 days**.
3. All dismantled materials shall be properly stored and handed over to NHDC authority.
4. The bid forms and schedule of items can be obtained from the website [www.nhdcltd.co.in](http://www.nhdcltd.co.in) and press notice is also available on website.

**Executive Director (Comm.)**

| Original Estimate |  |     |      |         |          |
|-------------------|--|-----|------|---------|----------|
| N/W               | Renovation of toilets in NHDC Limited office at 10th & 11th floor in Vikash Deep Building, Lucknow.  |     |      |         |          |
| SLNo              | Description  | Qty | Unit | Rate    | Amount   |
| 1                 | Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete :  |     |      |         |          |
| 1.1               | 300x16 mm  | 4   | each | 229.65  | 918.60   |
| 2                 | Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868 ) transparent or dyed to required colour or shade, with necessary screws etc. complete :   |     |      |         |          |
| 2.1               | 200x10 mm  | 4   | each | 79.25   | 317.00   |
| 3                 | Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :  |     |      |         |          |
| 3.1               | 125 mm   | 8   | each | 69.80   | 558.40   |
| 4                 | Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete.   |     |      |         |          |
| 4.1               | Twin rubber stopper  | 4   | each | 83.95   | 335.80   |
| 5                 | Providing and fixing to existing door frames.  |     |      |         |          |
| 5.1               | 24 mm thick factory made PVC door shutters made of styles and rails of a uPVC hollow section of size 59x24 mm and wall thickness 2 mm ( $\pm 0.2$ mm) with inbuilt edging on both sides. The styles and rails mitred and joint at the corners by means of M.S. galvanised/ plastic brackets of size 75x220 mm having wall thickness 1.0 mm and stainless steel screws. The styles of the shutter reinforced by inserting galvanised M.S. tube of size 20x20 mm and 1 mm ( $\pm 0.1$ mm) wall thickness. The lock rail made up of 'H' section, a uPVC hollow section of size 100x24 mm and 2 mm ( $\pm 0.2$ mm) wall thickness, fixed to the shutter styles by means of plastic/galvanised M.S. 'U' cleats. The shutter frame filled with a uPVC multi-chambered single panel of size not less than 620 mm, having over all thickness of 20 mm and 1 mm ( $\pm 0.1$ mm) wall thickness. The panels filled vertically and tie bar at two places by inserting horizontally 6 mm galvanised M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction of Engineer-in-charge. (For W.C. and bathroom door shutter). |     |      |         |          |
|                   |  | 8   | sqm  | 2718.60 | 21748.80 |

|      |   |     |       |        |           |
|------|---|-----|-------|--------|-----------|
| 6    | Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. | 120 | sqm   | 836.65 | 100398.00 |
| 7    | Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS : 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), including grouting the joints with white cement and matching pigments etc., complete.  | 72  | sqm   | 950.05 | 68403.60  |
| 8    | Painting with plaastic emulsion of approved brand and manufacture to give an even shade :   |     |       |        |           |
| 8.1  | Two or more coats on new work   | 260 | sqm   | 74.40  | 19344.00  |
| 9    | Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :   |     |       |        |           |
| 9.1  | One or more coats on old work   | 20  | sqm   | 48.50  | 970.00    |
|      | Wall painting with acrylic emulsion paint of approved brand and manufacture to give an even shade :   |     |       |        |           |
|      | Two or more coats on new work   | 200 | sqm   | 80.50  | 16100.00  |
|      | Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :  |     |       |        |           |
|      | Two or more coats on new work   | 50  | sqm   | 74.40  | 3720.00   |
|      | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.   | 200 | sqm   | 89.65  | 17930.00  |
| 10   | Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.  |     |       |        |           |
| 10.1 | For thickness of tiles 10 mm to 25 mm   | 120 | sqm   | 28.20  | 3384.00   |
| 11   | Dismantling G.I. pipes (external work) including excavation and refilling trenches after taking out the pipes, manually/ by mechanical means including stacking of pipes within 50 metres lead as per direction of Engineer-in-charge :   |     |       |        |           |
| 11.1 | 15 mm to 40 mm nominal bore   | 30  | metre | 57.85  | 1735.50   |

|        |   |    |       |         |          |
|--------|---|----|-------|---------|----------|
| 12     | Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required : |    |       |         |          |
| 12.1   | W.C. pan with ISI marked white solid plastic seat and lid   | 4  | each  | 3317.30 | 13269.20 |
| 13     | Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require:  |    |       |         |          |
| 13.1   | White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps   | 6  | each  | 2331.15 | 13986.90 |
| 14     | Providing and fixing water closet squatting pan (Indian type W.C. pan ) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required:    |    |       |         |          |
| 14.1   | White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests   | 2  | each  | 3392.80 | 6785.60  |
| 14     | Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing :   |    |       |         |          |
| 14.1   | Rectangular shape 453x357 mm  | 6  | each  | 727.90  | 4367.40  |
| 15     | Providing and fixing G.I. Pipes complete with G.I. fittings and clamps, i/c making good the walls etc. concealed pipe, including painting with anti corrosive bitumastic paint, cutting chases and making good the wall :   |    |       |         |          |
| 15.1   | 15 mm dia nominal bore  | 50 | metre | 306.05  | 15302.50 |
| 16     | Providing and fixing uplasticised PVC connection pipe with brass unions :   |    |       |         |          |
| 16.1   | 45 cm length  |    |       |         |          |
| 16.1.1 | 15 mm nominal bore  | 6  | each  | 68.60   | 411.60   |
| 17     | Providing and fixing G.I. Union in G.I. pipe including cutting and threading the pipe and making long screws etc. complete (New work) :   |    |       |         |          |
| 17.1   | 15 mm nominal bore  | 4  | each  | 165.25  | 661.00   |
| 18     | Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore   |    |       |         |          |
| 18.1   | 15mm nominal bore   | 6  | each  | 507.70  | 3046.20  |

|    |  |   |      |        |                  |
|----|--|---|------|--------|------------------|
| 19 | P/F swan neck pillar cock of approved quality in place of CP brass pillar trap.<br>a) 15mm.  | 6 | each | 500.00 | 3000.00          |
| 20 | Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved. | 6 | cum  | 123.70 | 742.20           |
| 21 | P/F CP JET pressure  | 1 | each | 600.00 | 600.00           |
| 22 | P/F CP angle valve Two way   | 1 | each | 800.00 | 800.00           |
| 23 | P/F CP bib cock-15mm   | 2 | each | 700.00 | 1400.00          |
| 24 | P/F PVC nahani trap- 100 x 100mm   | 2 | each | 300.00 | 600.00           |
| 25 | P/F PVC Tee- 100mm   | 1 | each | 300.00 | 300.00           |
| 26 | P/F PVC pipe - 100 mm  | 2 | mtr  | 275.00 | 550.00           |
| 27 | P/F Liquid soap container  | 3 | each | 800.00 | 2400.00          |
| 28 | P/F PVC waste pipe   | 3 | each | 100.00 | 300.00           |
| 29 | P/F CP Jali 100mm  | 4 | each | 50.00  | 200.00           |
|    | <b>Total</b>   |   |      |        | <b>324586.30</b> |